

## turbo® II Model 68-7" BULLNOSE

The original precleaner, variant for vertical mounting and/or under hood. The engine intake air activates the mechanical cleaning of the precleaner. No maintenance required. There is a lifetime warranty on the high-powered, highly efficient ejection spinner.

turbo® II Bullnose performs its job in the toughest environments day in and day out. The unique design is all about preventing micro-abrasive dust from entering the machine's engine creating cleaner air to prolong the engine life. turbo® II Bullnose is the industry standard precleaner by which all precleaners are judged.

From its durable metal construction to its high efficiency and low restriction across the entire range, turbo® II Bullnose is chosen worldwide by equipment operators for installation on loaders, graders, crushers, haulers, mixers, and mining machines. Anywhere a high level of protection is needed and where dust is an issue, the turbo® II Bullnose is a must.



<i>Art.nr</i>	<i>Weight</i>	<i>Height</i>	<i>CFM Range</i>	<i>Outside Diameter</i>	<i>Model number</i>	<i>Inlet Size Base</i>
<b>1-024-010</b>	2,2999999999999998224 kg	279 mm	100-250	203 mm	21-1024010	76 mm
<b>1-035-020</b>	2,9 kg	311 mm	250-350	235 mm	21-1035020	114 mm
<b>1-046-009</b>	4,90000000000000003553 kg	394 mm	300-700	311 mm	21-1046009	127 mm
<b>1-046-011</b>	3,9 kg	394 mm	300-700	311 mm	21-1046011	114 mm
<b>1-068-015</b>	7,3 kg	444 mm	700-1100	368 mm	21-1068015	152 mm
<b>1-068-016</b>	7,3 kg	444 mm	700-1100	368 mm	21-1068016	178 mm
<b>1-068-017</b>	7,3 kg	444 mm	700-1100	368 mm	21-1068017	203 mm