turbo® II Model 24-4" BULLNOSE

The original precleaner, variant for vertical mounting and/or under hood. The engine intake air activates the mechanical cleaning of the precleaner. No maintenance required. There is a lifetime warranty on the high-powered, highly efficient ejection spinner.

turbo® II Bullnose performs it's job in the toughest environments day in and day out. The unique design is all about preventing micro-abrasive dust from entering the machine's engine creating cleaner air to prolong the engine life. turbo® II Bullnose is the industry standard precleaner by which all precleaners are judged.

From its durable metal construction to its high efficiency and low restriction across the entire range, turbo® II Bullnose is chosen worldwide by equipment operators for installation on loaders, graders, crushers, haulers, mixers, and mining machines. Anywhere a high level of protection is needed and where dust is an issue, the turbo® II Bullnose is a must.

Article no.	*Weight*	*Height*	*CFM Range*	*Outside Diameter*	*Model number*	*Inlet Size Base*
1-024-010	2,2999999999999998224 kg	279 mm	100-250	203 mm	21-1024010	76 mm
1-035-020	2,9 kg	311 mm	250-350	235 mm	21-1035020	114 mm
1-046-009	4,9000000000000003553 kg	394 mm	300-700	311 mm	21-1046009	127 mm
1-046-011	3,9 kg	394 mm	300-700	311 mm	21-1046011	114 mm
1-068-015	7,3 kg	444 mm	700-1100	368 mm	21-1068015	152 mm
1-068-016	7,3 kg	444 mm	700-1100	368 mm	21-1068016	178 mm
1-068-017	7,3 kg	444 mm	700-1100	368 mm	21-1068017	203 mm

Sveadiesel AB
Trädgårdsgatan 21, 172 38 Sundbyberg
Telefon: 08-764 66 10 - E-post: mail@sveadiesel.se

SVEADIESEL INTER-TURBINE